



## **LEGRAND ZERO-U THREE PHASE PDU LCS<sup>3</sup> - 18XC13 + 6XC19 - IEC 60320 STANDARD**

Caracteristici tehnice

PDU Basic

IEC 60320 standard

18 C13 outlets + 6 C19 outlets with cord locking system

3 m Tensiune de alimentare cord with IEC60309 16 A 3P+N+E plug

Caracteristici generale

Legrand cabling system LCS<sup>3</sup> energy Distribution - three phase Zero-U Putere Distribution Units

To provide ~ electric Putere for IT equipment in 19" enclosures

Three phase Zero-U PDUs for vertical mounting in the cabinet

400 V - 50/60 Hz Tensiune de alimentare

Each circuit is protected by 16 A single pole MCB in a support with projecting edges to avoid accidental breakdown. 1 circuit per phase, each with 6 IEC 60320 C13 outlets and 2 IEC 60320 C19 outlets

330° rotating cable input for a perfect orientation of the cable and no interference in the cabinet

C13 and C19 standard outlets are equipped with cord locking system to avoid any accidental disconnection.

Universal solution compatible with all the cords (C14 plugs for C13 and C20 plugs for C19)

Delivered with 2 sets of metallic mounting brackets: button brackets (for quick fixing and variable pitch) and standard brackets (for screw fixing)

Black module (outlets and functions)

Aluminium profile

Pret: 1.915,04 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/zero-u-three-phase-pdu-lcs3-18xc13-6xc19-iec-60320-standard-237443>