



### PHILIPS HID ELECTROMAGNETIC BSN 100 K302-A2-ITS 230V 50HZ

#### General Information

Cod aplica?ie

K302-A2-ITS

Design

BC1-123

Tip lamp?

SON/CDO

Num?r de l?mpi

1 bucat?/unitate

#### Operating and Electrical

Tensiune de intrare

230 V

Frecven?? de intrare

50 Hz

Factor de putere sarcin? 100% (nom.)

0,85

Performan?? tensiune re?ea (CA)

-8%+6%

Siguran?? tensiune re?ea (CA)

-10%+10%

Curent de intrare cu corec?ie PF

0.6 A

Curent de intrare f?r? corec?ie PF

1.2 A

Factor de putere f?r? compensare PF (nom.)

0,4

Pierderi de putere (nom.)

13.7 W

Wiring

Lungime band? cabluri

6.0 mm

Sec?iune transversal? cablu contact balast

2.5 mm<sup>2</sup>

Tip conector

Screw

System characteristics

Putere nominal? lamp?-balast

100 W

Ignitor recomandat

for SON/CDO/CDM lamps ignitor SKD 578 (913700655366) or series digital SUD40 (913700193591) only

CDM

Temperature

T-Storage (max.)

130 °C

T-Storage (min.)

-30 °C

Bobinaj T (max.)

140 °C

Condi?ii normale Delta-T

60 °C

Approval and Application

Protec?ie activ? la temperatur?

Yes

M?rci de omologare

Marcaj CE

Certificat ENEC

Product Data

Cod complet produs

871869674086600

Nume comand? produs

BSN 100 K302-A2-ITS 230V 50Hz

EAN/UPC – Produs

8718696740866

Cod de comand?

74086600

Num?r?tor SAP – Cantitate per pachet

1

Num?r?tor SAP – Pachete per exterior

6

Material SAP

913700752326

Greutate net? SAP (bucat?)

1,400 kg

Pret: 67,59 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/hid-electromagnetic-bsn-100-k302-a2-its-230v-50hz-252411>