



PHILIPS IGNITORI SKD 578-S 220-240V 50/60HZ

General Information

Cod aplica?ie

578-S

Tip lamp?

SON/CDM/MH/HPI/HPA/CDO

Num?r de l?mpi

1 bucat?/unitate

Operating and Electrical

Tensiune de intrare

220 to 240 V

Frecven?? de intrare

De la 50 pan? la 60 Hz

Tip aprindere

Semi-Parallel

Incerc?ri aprindere

3

Num?r impulsuri de aprindere

1

Timp de aprindere (max.)

1185 s

Tensiune aprindere (max.)

5,00 kV

Tensiune aprindere (min.)

1,80 kV

Tensiune de r?spuns

190 V

Performan?? tensiune re?ea (CA)

-8%--+6%

Siguran?? tensiune re?ea (CA)

-10%--+10%

Pierderi de putere (nom.)

0.5 W

Wiring

Lungime band? cabluri

6.0 mm

Sec?iune transversal? cablu contact balast

0.50-2.50 mm²

Tip conector

Screw

System characteristics

Putere nominal? lamp?-balast

35-600 W

Temperature

T-Ambient (max.)

85 °C

T-Ambient (min.)

-30 °C

T-Storage (max.)

85 °C

T-Storage (min.)

-35 °C

Maximum T-case (max.)

90 °C

Approval and Application

M?rci de omologare

Marcaj CE

Certificat ENEC

Product Data

Cod complet produs

872790089569800

Nume comand? produs

SKD 578-S 220-240V 50/60Hz

EAN/UPC – Produs

8711500881779

Cod de comand?

89569800

Num?r?tor SAP – Cantitate per pachet

1

Num?r?tor SAP – Pachete per exterior

20

Material SAP

913700655466

Greutate net? SAP (bucat?)

31,400 g

Pret: 18,03 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/ignitori-skd-578-s-220-240v-50-60hz-252438>