



### **SCHRACK APLICA KARO LED 12W 1080LM 4000K IP44 ECHIPATA CU KIT EM.3H**

EAN-Code 9004840802429

In?ime 95,00mm

Diametru 280,00mm

Mas? net? 0,46kg.

Temperatura minim? a mediului ambient 0°C

Temperatura maxim? a mediului ambient 35°C

Tip iluminare corp iluminat de perete, iluminat pentru tavan

Montaj Montaj de perete, Montaj incastat in plafon

Culoare alb

Material PMMA, tabl? de o?el

Fabricant 01-Schrack-Trinity

Balast LED driver

Tensiune de alimentare AC 220-240V

Dulie lamp? LED Platine

Watt 18W

Eficien?? sistem 90lm/W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Lumeni 1620lm

Flux luminos in mod emergen?? 500lm

Durat? de via?? 40.000h / L80 / B50

Dimabil nu

Clas? de protec?ie I

Grad de protec?ie IP44

Rezisten?a la ?oc IK02

Surse de lumin? incluse da

Pachete disponibile 1 buc.

Pret: 564,80 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/aplica-karo-led-12w-1080lm-4000k-ip44-echipata-cu-kit-em-3h-255683>