



SCHRACK ARKTUR ECO II 150W 840 24000LM 1-10V IP65 110°, NEGRU

EAN-Code 9004840878868

Lungime 125,00mm

L??ime net? 330,00mm

In?ime 171,00mm

Diametru 330,00mm

Mas? net? 3,70kg.

CLAS? ENERGIE D

Temperatura minim? a mediului ambient -35°C

Temperatura maxim? a mediului ambient 50°C

Tip iluminare downlight, high-bay luminaire, pendulum luminaire

Montaj Montaj incastrat in plafon, Pendul

Culoare negru

Material aluminiu, Hardened glass

Protec?ie la supratensiuni 4kV

Fabricant 01-Schrack-Trinity

Unghiul de radia?ie 110°

Indice de orbire (UGR) 34

Balast LED driver

Tensiune de alimentare AC 100-240V

Dulie lamp? LED Platine

Watt 150W

Eficien?? sistem 160lm/W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Lumeni 24000lm

Candela 8630

Durat? de via?? 50.000h / L70 / B50

Dimabil da

Clas? de protec?ie I

Grad de protec?ie IP65

Clas? energetic? D

Rezisten?a la ?oc IK07

Surse de lumin? incluse da

Fire protection marking D

Pachete disponibile 1 buc.

Pret: 786,78 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/arktur-eco-ii-150w-840-24000lm-1-10v-ip65-1100-negru-255733>