



## **SCHRACK ARKTUR ROUND II 130W, 17000LM, 4000K, 120°, DALI**

EAN-Code 9004840845679

In?ime 114,00mm

Diametru 380,00mm

Mas? net? 6,00kg.

CLAS? ENERGIE A

Temperatura minim? a mediului ambient -20°C

Temperatura maxim? a mediului ambient 50°C

Tip iluminare downlight, high-bay luminaire, pendulum luminaire

Montaj Montaj incastrat in plafon, Pendul

Culoare RAL 9006 (gri)

Material aluminiu, Polycarbonat

Fabricant 01-Schrack-Trinity

Unghiul de radia?ie 120°

Balast LED driver

Tensiune de alimentare AC 230V

Dulie lamp? LED Platine

Watt 130W

Eficien?? sistem 131lm/W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Lumeni 17000lm

Num?r l?mpi 1

Durat? de via?? 60.000h / L80 / B10

Dimabil DALI

Clas? de protec?ie I

Grad de protec?ie IP65

Clas? energetic? A  
Rezisten?a la ?oc IK10  
Surse de lumin? incluse da  
Pachete disponibile 1 buc.  
Pret: 3.010,68 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/arktur-round-ii-130w-17000lm-4000k-1200-dali-255736>