



### **SCHRACK ARKTUR SQUARE LED 105W 11400LM/840 ECG IP66 120X40° GRAY**

EAN-Code 9004840569728

Lungime 515,00mm

Lungime net? 345,00mm

Inaltime 90,00mm

Mas? net? 6,50kg.

Temperatura minim? a mediului ambient -40°C

Temperatura maxim? a mediului ambient 45°C

Tip iluminare downlight, high-bay luminaire, pendulum luminaire

Montaj Montaj incastrat in plafon, Pendul

Culoare gri

Material Die-cast aluminum, Hardened glass

Protec?ie la supratensiuni 6kV

Fabricant 01-Schrack-Trinity

Unghiul de radia?ie 40°

Balast insert electronic EVG

Tensiune de alimentare AC 220-240V

Dulie lamp? LED Platine

Watt 105W

Eficien?? sistem 109lm/W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Lumeni 11950lm

Durat? de via?? 100.000h / L80 / B10

Dimabil nu

Clas? de protec?ie I

Grad de protec?ie IP66

Rezistența la șoc IK07

Surse de lumină incluse da

Numbers of luminars per MCB B10 4

Numbers of luminars per MCB B13 5

Numbers of luminars per MCB B16 7

Numbers of luminars per MCB B20 8

Numbers of luminars per MCB B25 10

Numbers of luminars per MCB C10 7

Numbers of luminars per MCB C13 9

Numbers of luminars per MCB C16 11

Numbers of luminars per MCB C20 14

Numbers of luminars per MCB C25 18

Pachete disponibile 1 buc.

Pret: 1.948,00 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/arktur-square-led-105w-11400lm-840-ecg-ip66-120x400-gray-255738>