



SCHRACK DEVO PRO II 44W 6100LM 840 230V ECG IP66 CL 1 PMMA 1500MM

EAN-Code 9004840879322

Lungime 1500,00mm

Lungime net? 86,00mm

Inaltime 95,00mm

Mas? net? 2,61kg.

CLAS? ENERGIE D

Temperatura minim? a mediului ambient -20°C

Temperatura maxim? a mediului ambient 35°C

Tip iluminare downlight, pendulum luminaire, wall luminaires

Montaj Montaj de perete, Montaj incastat in plafon, Pendul

Culoare gri deschis

Material Glass fibre reinforced polyester

Masc? PMMA opal

Fabricant 01-Schrack-Trinity

Balast LED driver

Tensiune de alimentare AC 230V

Dulie lamp? LED Platine

Watt 44W/30W/37W/51W

Eficien?? sistem 139lm/W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Lumeni 6300lm/4300lm/5400lm/7000lm

Durat? de via?? 50.000h / L70 / B50

Dimabil nu

Clas? de protec?ie I

Grad de protec?ie IP66

Clas? energetic? D

Rezisten?a la ?oc IK03

Surse de lumin? incluse da

Fire protection marking D

Numbers of luminars per MCB B10 15

Numbers of luminars per MCB B13 20

Numbers of luminars per MCB B16 25

Numbers of luminars per MCB B20 31

Numbers of luminars per MCB B25 39

Numbers of luminars per MCB C10 24

Numbers of luminars per MCB C13 33

Numbers of luminars per MCB C16 38

Numbers of luminars per MCB C20 52

Numbers of luminars per MCB C25 65

Pachete disponibile 1 buc., 72 buc.

Pret: 343,50 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/devo-pro-ii-44w-6100lm-840-230v-ecg-ip66-cl-1-pmma-1500mm-261037>