



SCHRACK KARO II LED 18W 3000K 230V 120° 1390LM, SENZOR

EAN-Code 9004840838169

In?ime 105,00mm

Diametru 360,00mm

Mas? net? 0,75kg.

Temperatura minim? a mediului ambient -20°C

Temperatura maxim? a mediului ambient 40°C

Tip iluminare downlight, wall luminaires

Montaj Montaj de perete, Montaj incastat in plafon

Culoare alb

Material tabl? de o?el

Masc? PMMA opal

Fabricant 01-Schrack-Trinity

Unghiul de radia?ie 120°

Balast LED driver

Tensiune de alimentare AC 220-240V

Dulie lamp? LED Platine

Watt 18W

Eficien?? sistem 77lm/W

Culoare lumin? alb cald

Temperatura culorii 3000K

Indice redare culoare ?80

Stabilitatea culorii MacAdam

Lumeni 1390lm

Durat? de via?? 45.000h / L70 / B50

Dimabil nu

Clas? de protec?ie I

Grad de protec?ie IP44

Rezistența la șoc IK02

Surse de lumină incluse da

Domeniu sesizare 2-6m.

Unghi de detectie 150°

Numbers of luminars per MCB B10 70

Numbers of luminars per MCB B13 90

Numbers of luminars per MCB B16 110

Numbers of luminars per MCB B20 140

Numbers of luminars per MCB B25 170

Numbers of luminars per MCB C10 70

Numbers of luminars per MCB C13 90

Numbers of luminars per MCB C16 110

Numbers of luminars per MCB C20 140

Numbers of luminars per MCB C25 170

Pachete disponibile 1 buc., 5 buc.

Pret: 162,79 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/karo-ii-led-18w-3000k-230v-1200-1390lm-senzor-266196>