



SCHRACK KARO II LED, 18W, 1530LM, 4000K, 230V, IP44, 120°

EAN-Code 9004840838114

In?ime 105,00mm

Diametru 360,00mm

Mas? net? 0,55kg.

Temperatura minim? a mediului ambient -20°C

Temperatura maxim? a mediului ambient 40°C

Tip iluminare downlight, wall luminaires

Montaj Montaj de perete, Montaj incastat in plafon

Culoare alb

Material tabl? de o?el

Masc? PMMA opal

Fabricant 01-Schrack-Trinity

Unghiul de radia?ie 120°

Balast LED driver

Tensiune de alimentare AC 220-240V

Dulie lamp? LED Platine

Watt 18W

Eficien?? sistem 85lm/W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Stabilitatea culorii MacAdam

Lumeni 1530lm

Durat? de via?? 45.000h / L70 / B50

Dimabil nu

Clas? de protec?ie I

Grad de protec?ie IP44

Rezistența la șoc IK02

Surse de lumină incluse da

Numbers of luminars per MCB B10 71

Numbers of luminars per MCB B13 92

Numbers of luminars per MCB B16 114

Numbers of luminars per MCB B20 142

Numbers of luminars per MCB B25 178

Numbers of luminars per MCB C10 71

Numbers of luminars per MCB C13 92

Numbers of luminars per MCB C16 114

Numbers of luminars per MCB C20 142

Numbers of luminars per MCB C25 178

Pachete disponibile 1 buc., 5 buc.

Pret: 106,24 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/karo-ii-led-18w-1530lm-4000k-230v-ip44-1200-266197>