



SCHRACK KARO II LED, 22W, 1980LM, 4000K, IP44, 230V, 120°

EAN-Code 9004840862607, 9004840862645

In?ime 115,00mm

Diametru 410,00mm

Mas? net? 1,45kg.

Temperatura minim? a mediului ambient -20°C

Temperatura maxim? a mediului ambient 40°C

Tip iluminare downlight, wall luminaires

Montaj Montaj de perete, Montaj incastat in plafon

Culoare alb

Material tabl? de o?el

Masc? PMMA opal

Fabricant 01-Schrack-Trinity

Unghiul de radia?ie 120°

Balast LED driver

Tensiune de alimentare AC 220-240V

Dulie lamp? LED Platine

Watt 22W

Eficien?? sistem 77lm/W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Stabilitatea culorii MacAdam

Lumeni 1980lm

Durat? de via?? 45.000h / L70 / B50

Dimabil nu

Clas? de protec?ie I

Grad de protec?ie IP44

Rezistența la șoc IK02

Surse de lumină incluse da

Numbers of luminars per MCB B10 55

Numbers of luminars per MCB B13 70

Numbers of luminars per MCB B16 90

Numbers of luminars per MCB B20 110

Numbers of luminars per MCB B25 140

Numbers of luminars per MCB C10 55

Numbers of luminars per MCB C13 70

Numbers of luminars per MCB C16 90

Numbers of luminars per MCB C20 110

Numbers of luminars per MCB C25 140

Pachete disponibile 1 buc., 5 buc.

Pret: 138,19 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/karo-ii-led-22w-1980lm-4000k-ip44-230v-1200-266200>