



SCHRACK KARO LED, 14W, 3000K, 1244LM, OPAL, PMMA, IP44, EMERGENCY

EAN-Code 9004840887440

In?ime 90,00mm

Diametru 280,00mm

Mas? net? 0,46kg.

Temperatura minim? a mediului ambient 0°C

Temperatura maxim? a mediului ambient 35°C

Tip iluminare corp iluminat de perete, iluminat pentru tavan

Montaj Montaj de perete, Montaj incastat in plafon

Culoare alb

Material PMMA, tabl? de o?el

Fabricant 01-Schrack-Trinity

Balast LED driver

Tensiune de alimentare AC 220-240V

Dulie lamp? LED Platine

Watt 14W

Eficien?? sistem 89lm/W

Culoare lumin? alb cald

Temperatura culorii 3000K

Indice redare culoare ?80

Lumeni 1244lm

Flux luminos in mod emergen?? 450lm

Durat? de via?? 50.000h / L70 / B50

Dimabil nu

Clas? de protec?ie I

Grad de protec?ie IP44

Rezisten?a la ?oc IK02

Surse de lumin? incluse da

Pachete disponibile 1 buc.

Pret: 598,25 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/karo-led-14w-3000k-1244lm-opal-pmma-ip44-emergency-266208>