



SCHRACK PARC II LED 35W 4600LM 740 IP66 ROTATIONAL SIMETRIC, GRAFIT

EAN-Code 9004840843385

In?ime 482,00mm

Diametru 360,00mm

Mas? net? 4,40kg.

Temperatura minim? a mediului ambient -40°C

Temperatura maxim? a mediului ambient 50°C

Tip iluminare street light

Protec?ie la supratensiuni 6kV

Montaj Montaj catarg

Culoare grafit

Material Die-cast aluminum, Polycarbonat

Masc? clar

Fabricant 01-Schrack-Trinity

Balast insert electronic EVG

Tensiune de alimentare AC 220-240V

Surs? iluminare LED

Dulie lamp? LED Platine

Watt 35W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?70

Lumeni 4600lm

Durat? de via?? 100.000h / L80 / B10

Dimabil nu

Clas? de protec?ie II

Grad de protec?ie IP66

Rezisten?a la ?oc IK08

Pigtail 76mm

Expunere la vant 0,088m²

Gama de temperatur? - Func?ionare -40 la +50°C

Pachete disponibile 1 buc.

Pret: 2.221,33 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/parc-ii-led-35w-4600lm-740-ip66-rotational-simetric-grafit-271025>