



SCHRACK PIKO LED 6.5W 3000K 230V 40° 655LM ALB

EAN-Code 9004840872453

In?ime 43,80mm

Diametru 85,00mm

Mas? net? 0,09kg.

Temperatura minim? a mediului ambient -20°C

Temperatura maxim? a mediului ambient 40°C

Decupaj mm O68-75mm

Tip iluminare downlight

Montaj Montaj incastat in plafon

Culoare alb

Material PC

Masc? opal

Fabricant 01-Schrack-Trinity

Unghiul de radia?ie 40°

Balast LED driver

Tensiune de alimentare AC 220-240V

Dulie lamp? LED Platine

Watt 6,5W

Eficien?? sistem 85lm/W

Culoare lumin? alb cald

Temperatura culorii 3000K

Indice redare culoare ?80

Lumeni 550lm

In?ime 43,80mm

Durat? de via?? 45.000h / L70 / B50

Dimabil nu

Clas? de protec?ie II

Grad de protecție IP20

Rezistența la șoc IK03

Surse de lumină incluse da

Numbers of luminars per MCB B10 110

Numbers of luminars per MCB B13 140

Numbers of luminars per MCB B16 170

Numbers of luminars per MCB B20 220

Numbers of luminars per MCB B25 270

Numbers of luminars per MCB C10 110

Numbers of luminars per MCB C13 140

Numbers of luminars per MCB C16 170

Numbers of luminars per MCB C20 220

Numbers of luminars per MCB C25 270

Pachete disponibile 1 buc., 60 buc.

Pret: 48,19 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/piko-led-6-5w-3000k-230v-400-655lm-alb-272115>