



### **SCHRACK PRIMOLUX LED 1235 54W 5900LM/840 3H M OPAL ECG IP44 WHITE**

EAN-Code 9004840571462

Lungime 1235,00mm

Lungime net? 95,00mm

Inaltime 72,00mm

Mas? net? 3,20kg.

Temperatura minim? a mediului ambient 0°C

Temperatura maxim? a mediului ambient 30°C

Tip iluminare downlight

Montaj Montaj incastrat in plafon

Culoare alb

Material PMMA opal, tabl? de o?el

Masc? opal

Fabricant 01-Schrack-Trinity

Balast LED driver

Tensiune de alimentare AC 220-240V

Dulie lamp? LED Platine

Watt 53W

Eficien?? sistem 125lm/W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Lumeni 6650lm

Iluminat de siguran?? Emergency kit 3h

Flux luminos in mod emergen?? 370lm

Durat? de via?? 60.000h / L80 / B10

Dimabil nu

Clas? de protec?ie I

Grad de protecție IP44  
Rezistența la șoc IK05  
Surse de lumină incluse da  
Pachete disponibile 1 buc.  
Pret: 1.785,81 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/primolux-led-1235-54w-5900lm-840-3h-m-opal-ecg-ip44-white-272688>