



### **SCHRACK PRIMOLUX LED 1535 68W 8000LM/840 OPAL DALI IP44 WHITE**

EAN-Code 9004840571547

Lungime 1535,00mm

Lungime net? 95,00mm

Inaltime 72,00mm

Mas? net? 3,10kg.

Temperatura minim? a mediului ambient 0°C

Temperatura maxim? a mediului ambient 30°C

Tip iluminare downlight

Montaj Montaj de perete, Montaj incastat in plafon

Culoare alb

Material PMMA opal, tabl? de o?el

Fabricant 01-Schrack-Trinity

Balast EVG DALI

Tensiune de alimentare AC 220-240V

Dulie lamp? LED Platine

Watt 65W

Eficien?? sistem 132lm/W

Culoare lumin? neutral white

Temperatura culorii 4000K

Indice redare culoare ?80

Lumeni 8600lm

Durat? de via?? 60.000h / L80 / B10

Dimabil DALI

Clas? de protec?ie I

Grad de protec?ie IP44

Rezisten?a la ?oc IK05

Surse de lumin? incluse da

Pachete disponibile 1 buc.

Pret: 1.254,44 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/primolux-led-1535-68w-8000lm-840-opal-dali-ip44-white-272691>