



## **ZALUX LAMPA LINIARA ETANSA CU FIXARE RAPIDA BHE 69K 1.2 40-840 ET BPM** **3M**

Gas-tight, long-lasting, compact and resistant luminaire with easy installation  
Single-part IP66 / IP69K extruded PMMA profile, up to 138lm/W and flicker free.  
Gas tight: hermetically sealed against liquid and gas income.  
PWIS-free to guarantee a perfect finish in paint shops and coating areas.  
Quick and safe mounting with no tools needed.  
Extraordinary chemical resistance.

Downloads

Features

Mechanical

Profile Extruded PMMA with UV protection, upper part grey RAL 7035, bottom part opal

End caps Acrylonitrile styrene acrylate (ASA)

Gasket PWISS-free silicone

Cable entry Cable gland with external cable

Fixing clips Stainless steel

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 4,000 lm

Power 29 W

Efficiency 135 lm/W

Functional

Lifetime L80 70,000 Custom.U1 at 25°C

Fire protection GRP and PMMA / Flammability (UL94): HB

Glow wire test (EN 60695-2-11): 650°C

Electrical

Driver non dimmable

Connection External cable 3m

Flicker factor < 1%

Power factor > 0.95 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 1,200 mm

Distance between springs (Xm) 800 mm

Width (Y) 76 mm

Height (Z) 67 mm

Weight 2 kg

<span class="elementor-button-text"

Pret: 510,83 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa- liniara-etansa-cu-fixare-rapida-bhe-69k-1-2-40-840-et-bpm-3m-287553>