



## **ZALUX LAMPA LINIARA ETANSA CU FIXARE RAPIDA BST 1.2 37-840 ET BPC**

Long-lasting, compact and resistant luminaire with easy installation  
Single-part IP66 / IP69K extruded polycarbonate profile, with up to 115 lm/W  
PWIS-free to guarantee a perfect finish in paint shops and coating areas.  
Quick and safe mounting with no tools needed.  
Compact design to optimize logistic costs

Downloads

Features

Mechanical

Profile Extruded polycarbonate with UV protection, upper part grey RAL 7035, bottom part opal

End caps Injected polycarbonate

Gasket PWISS-free silicone

Cable entry Cable gland

Fixing clips Stainless steel

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 3,700 lm

Power 32 W

Efficiency 115 lm/W

Functional

Lifetime L70 35,000 h at 25°C

Fire protection PC / Flammability (UL94): V2

Glow wire test (EN 60695-2-11): 850°C

Electrical

Driver Electronic transformer, switchable

Connection Terminal block

Flicker factor 5%

Power factor > 0.90 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 1,213 mm

Distance between springs (Xm) 800 mm

Width (Y) 76 mm

Height (Z) 67 mm

Weight 1.8 kg

<span class="elementor-button-text"

Pret: 168,05 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa- liniara-etansa-cu-fixare-rapida-bst-1-2-37-840-et-bpc-287566>