



ZALUX LAMPA LINIARA ETANSA CU FIXARE RAPIDA BSTP 0.6 20-840 ET BPC

Long-lasting, compact and resistant luminaire with easy installation

Single-part IP66 / IP69K extruded polycarbonate profile, up to 125 m/W and flicker free.

PWIS-free to guarantee a perfect finish in paint shops and coating areas.

Quick and safe mounting with no tools needed: cable gland and connector fixed to the gear tray by a patented piece.

Customizable end caps

Downloads

Features

Mechanical

Profile Extruded polycarbonate with UV protection, upper part grey RAL 7035, bottom part opal

End caps Injected polycarbonate

Gasket PWISS-free silicone

Cable entry Cable gland

Fixing clips Stainless steel

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 2,000 lm

Power 17 W

Efficiency 120 lm/W

Functional

Lifetime L80 50,000 h at 25°C

Fire protection PC / Flammability (UL94): V2

Glow wire test (EN 60695-2-11): 850°C

Electrical

Driver non dimmable

Connection Terminal block

Flicker factor < 1%

Power factor > 0.95 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 637 mm

Distance between springs (Xm) 350 mm

Width (Y) 76 mm

Height (Z) 67 mm

Weight 1 kg

<span class="elementor-button-text"

Pret: 191,46 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa- liniara-etansa-cu-fixare-rapida-bstp-0-6-20-840-et-bpc-287570>