



ZALUX LAMPA LINIARA TIP FIPAD DST 1.5 60-840 ET PC DPC PA-U

Flexible to choose the right components in a versatile luminaire suitable from basic to the most demanding applications.

Quick, easy and safe mounting in ceiling, wall or suspended.

Polyurethane continuous gasket specific for IP66 for a full protection against degradation, thanks to its manufacturing and drying processes.

HACCP conformity guarantees safe use where foods are processed, handled and packed..

Specific slimmer diffuser for LED modules

Downloads

Features

Mechanical

Housing Injected polycarbonate with UV protection, grey RAL 7035

Diffuser Injected polycarbonate with UV protection, frosted finish

Gasket Polyurethane

Cable entry Grommet

Closing clips Polyamide 6 unremovable

Fixing clips Stainless steel

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 6,100 lm

Power 47 W

Efficiency 130 lm/W

Functional

Lifetime L70 35,000 h at 25°C

Fire protection PC / Flammability (UL94): V2

Glow wire test (EN 60695-2-11): 850°C

Electrical

Driver non dimmable
Connection 3 pole push wire terminal block
Flicker factor 5%
Power factor > 0.90 full load
Photometrical
Colour consistency < 4 SDCM
Dimensions
Length (X) 1,573 mm
Distance between springs (Xm) 1,100 mm
Width (Y) 101 mm
Height (Z) 84 mm
Weight 2.2 kg

Pret: 212,36 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa- liniara-tip-fipad-dst-1-5-60-840-et-pc-dpc-pa-u-287611>