



ZALUX LAMPA LINIARA TIP FIPAD DSTP 1.2 40-840 ET PC DPC IX-U

Versatile luminaire with up to 145lm/W
Flicker-free for a high quality lighting.
Unremovable stainless steel or plastic closing clips for enhanced safety.
High impact protection and easy mounting.
First-class raw materials safe against premature deterioration.

Downloads

Features

Mechanical

Housing Injected polycarbonate with UV protection, grey RAL 7035

Diffuser Injected polycarbonate with UV protection, frosted finish

Gasket Polyurethane

Cable entry Grommet

Closing clips Stainless steel unremovable

Fixing clips Stainless steel

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 4,000 lm

Power 28 W

Efficiency 145 lm/W

Functional

Lifetime L80 50,000 h at 25°C

Fire protection PC / Flammability (UL94): V2

Glow wire test (EN 60695-2-11): 850°C

Electrical

Driver non dimmable

Connection 3 pole push wire terminal block

Flicker factor < 1%

Power factor > 0.95 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 1,277 mm

Distance between springs (Xm) 800 mm

Width (Y) 101 mm

Height (Z) 84 mm

Weight 1.7 kg

<span class="elementor-button-text"

Pret: 253,32 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa- liniara-tip-fipad-dstp-1-2-40-840-et-pc-dpc-ix-u-287613>