



ZALUX LAMPA LINIARA ETANSA CU FIXARE RAPIDA KHE 1.5 60-840 ET PC

The protected luminaire ready for the future

Robust for a wide range of temperature, up to 55°C

KE combines the best of extrusion and injection luminaires offering high endurance and fully adaptability

Innovative lever locking system, for a quick and safe mounting and prepared for vandal-proof environments

Quick and safe connection with up to 8 poles ready for through wiring, phase connection, emergency and so on

Downloads

Features

Mechanical

Profile Extruded polycarbonate with UV protection, upper part dark grey RAL 7046

End caps Injected polycarbonate

Gasket Removable and recyclable thermoplastic elastomers

Cable entry Cable gland

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 6,000 lm

Power 41 W

Efficiency 147 lm/W

Functional

Fire protection PC / Flammability (UL94): V2

Glow wire test (EN 60695-2-11): 850°C

Electrical

Connection 3-8 poles WAGO quick connector

Flicker factor < 1%

Power factor > 0.95 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 1,664 mm

Distance between springs (Xm) 1,100 mm

Width (Y) 120 mm

Height (Z) 100 mm

Weight 3.6 kg

<span class="elementor-button-text"

Pret: 433,07 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa- liniara-etansa-cu-fixare-rapida-khe-1-5-60-840-et-pc-287662>