



## **ZALUX LAMPA PENTRU MEDII HIPERCLORURATE SI ÎN AER LIBER STRONGERTUBE G2 B 6500-840 ET PMMA ZB**

For hyper chlorinated environments and outdoor

Specific potting for a full tight sealing to avoid the penetration of gases and water.

Safe against the corrosion of LED modules and electronic components.

High thickness PMMA resistant to chemicals and robust for a durable use in outdoor.

End caps with great thermal stability to resist UV radiation, heat, water, ageing and chemicals.

Downloads

Features

Mechanical

Profile High thickness PMMA

End caps Acrylonitrile styrene acrylate (ASA)

Gasket Polyurethane

Cable entry Cable gland with external cable

Fixing clips Specific stainless steel fixing brackets

Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 6,500 lm

Power 43 W

Efficiency 150 lm/W

Functional

Lifetime L80 100,000 h at 35°C

Fire protection PMMA / Flammability (UL94): HB

Glow wire test (EN 60695-2-11): 650°C

Electrical

Driver non dimmable

Connection 3 pole push wire terminal block

Flicker factor < 1%

Power factor > 0.95 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 1,340 mm

Distance between springs (Xm) 1,205 mm

Width (Y) 112 mm

Height (Z) 112 mm

Weight 4.6 kg

<span class="elementor-button-text"

Pret: 1.104,42 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa-pentru-medii-hiperclorurate-si-in-aer-liber-strongertube-g2-b-6500-840-et-pmma-zb-287797>