



## **ZALUX LAMPA ATEX PENTRU MEDII HIPERCLORURATE SI ÎN AER LIBER** **IK26STRONGEX2 300 B 15-840 ET CG**

Extreme robustness and resistance against impacts and chemical agents  
High performance LED module and driver, with high resistance to high temperatures up to 55°C.  
Specific gas tight potting to avoid the ingress and condensation of gases.  
Resistant to acids, sulphur vapours and salty environments.  
Suitable for outdoor without limitations.

### Downloads

Zone 2, 22

Ex II 3G Ex ec IIC T5/T6 Gc

Ex II 3D Ex tc IIIC T85...T100 Dc

ATEX certificate No: OBAC 20 ATEX 0334X

### Features

#### Mechanical

Profile High impacts resistant PMMA

End caps PA66 + fibreglass

Gasket Polyurethane

Cable entry ATEX cable gland

Fixing clips Specific stainless steel fixing brackets

#### Operational Data

Light colour 4,000 K

CRI >80

Luminous flux 1,500 lm

Power 10 W

Efficiency 150 lm/W

#### Functional

Lifetime L80 100,000 h at 35°C

Fire protection PMMA / Flammability (UL94): V2

Glow wire test (EN 60695-2-11): 650°C

Electrical

Driver non dimmable

Connection External cable 1m

Power factor > 0.95 full load

Photometrical

Colour consistency < 3 SDCM

Dimensions

Length (X) 435 mm

Distance between springs (Xm) 300 mm

Width (Y) 127 mm

Height (Z) 113 mm

Weight 2 kg

<span class="elementor-button-text"

Pret: 783,80 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/lampa-atex-pentru-medii-hiperclorurate-si-in-aer-liber-ik26strongex2-300-b-15-840-et-cg-287820>