



SCHNEIDER NEW UNICA - COVER FRAME + FIXING FRAME - 2 GANGS - 2 X 10 MODULES - ALUMINIUM

Schneider Electric New Unica cover frame NU021030 is in color aluminium. This cover frame has 2 gangs. Being made of thermoplastic ABS-UV stabilised material, this cover frame is quite reliable and resistant. Besides, it reaches IK04 protection level, which can help protect against impact. Also, being environment-friendly, this device reached UV resistant, acetone, alcohol, ammonia, bleach, liquid soap, oil, petrol, window-cleaning fluid. This cover frame is SVHC (substances of very high concern) free too. This cover frame belongs to Unica System+ aesthetic group. What's more, it well satisfied the standard of IEC 60669-1, IEC 60884-1. It is 300 mm in width, 165 mm in height and 10 mm in depth. Besides, it is halogen free halogen free, which is good for your health. The device's fixing mode is clip-in with 2 x 10 modules. And the product weighs 0.34 kg. Unica includes a suite of new designs, colors and materials. Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

range - New Unica

device application - Mounting

product or component type - Cover frame

aesthetic name - Unica System+

number of gangs - 2 gangs

installation direction - Horizontal

type of frame - Double

number of modules - 2 x 10 modules

fixing mode - Clip-in

colour tint - Aluminium

Complementary

provided equipment - Fixing frame

material - Thermoplastic ABS-UV stabilised: cover frame

standards - IEC 60669-1

IEC 60884-1

width - 300 mm

height - 165 mm

depth - 10 mm

net weight - 0.34 kg

resistance to chemical agents - Resistant to alcohol (70 %)

Resistant to alcohol (96 %)

Resistant to A-Lactic Acid

Resistant to diluted quaternary ammonium

Resistant to diluted bleach

Resistant to diluted ammonia

Resistant to soapy water

Resistant to crystal cleaner

Resistant to hydrogen peroxide 10 volumes

Resistant to hexane

Environment

IK degree of protection - IK04

IP degree of protection - IP21D

Packing Units

Unit Type of Package 1 - PCE

Package 1 Length - 30.0 cm

Number of Units in Package 1 - 1

Package 2 Width - 30 cm

Package 2 Height - 15 cm

Package 2 Weight - 1.52 kg

Package 3 Height - 77 cm

Package 1 Width - 16.5 cm

Package 1 Height - 1.0 cm

Package 1 Weight - 361.0 g

Number of Units in Package 2 - 3

Unit Type of Package 2 - S02

Package 2 Length - 40 cm

arrow2_down

Pret: 0,00 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/new-unica-cover-frame-fixing-frame-2-gangs-2-x-10-modules-aluminium-292519>