



IEK INPUT TERMINAL PENTRU KVM MODULAR EQUIPMENT 4-25MM2 (SIDE INPUT)

Used to connect conductors to modular equipment. Central connection of conductors. Convenient connection of conductors to terminal clamps of modular devices when using connecting buses.

The flat terminal output provides reliable electrical contact with the connecting bus terminal.

Possibility of summing up conductors of large cross-section up to 25 mm². Connectable conductor cross section solid-core: 4...25

Connectable conductor cross section multi-wired: 4...25

Rated current In: 100

Nominal rated voltage: 400

Type of electrical connection 2: EV000415

Connection position: EV001224

Number of poles: 1

Number of clamp positions per pole: 1

Mounting method: EV005276

Material insulation body: EV000139

Operation temperature: -40...+50

Inflammability class of insulation material acc. with UL94: EV004430

Width/grid dimension: 13.5

Length: 35

Colour: EV000202

Nominal operating AC voltage U_e: 400

Nominal DC operating voltage U_e: 220

Nominal frequency: 50

Rated insulation voltage U_i: 415

Max. conductor cross section: 25

Material clamp: EV000149

Material housing: EV000139

Ambient class: IEK_V0000009

Width: 13,5

Height: 19

Nominal Attachment Capacity: 4...25

Tightening torque Nm at conductor section: 2,5

Quantity in the kit: 100

Model: EV005828

Minimum section: 16.0

Attachment screw: ?8

Current-carrying part material: EV000138

Type of electrical connection 1: EV000415

Pret: 7,11 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/input-terminal-pentru-kvm-modular-equipment-4-25mm2-side-input-308970>