





IEK CLEMA ZNI-4MM2 (JXB35A) GRI

These terminal blocks serve for safe and compact connection of phase, neutral and protective (ground) conductors of various size. They are installed onto a DIN-rail. The set is completed with a marking band for number inscription and side blinds for ZNI series screw terminal blocks. Color: blue, gray, green. Terminal clamps can be covered with plastic blinds of correspondent size and color. They are made of colorednon-inflammablepolyamide of yellowish-green (grounding), blue (neutral), gray and green (phase) color. The set is completed with a marking band for number inscription.

They are made of colored non-inflammable polyamide. Connectable conductor cross section solid-core: 0,2...6

Connectable conductor cross section multi-wired: 0,2...4

Rated current In: 35

Nominal rated voltage: 600

Type of electrical connection 2: EV000415

Connection position: EV001224

Number of poles: 1

Number of clamp positions per pole: 2

Mounting method: EV005503

Material insulation body: EV000402 Operation temperature: -40...+80

Inflammability class of insulation material acc. with UL94: EV004429

Width/grid dimension: 6.3

Length: 41,5

Colour: EV000270

Nominal operating AC voltage Ue: 600 Nominal DC operating voltage Ue: 440

Nominal frequency: 50

Rated insulation voltage Ui: 660 Max. conductor cross section: 4

Material clamp: EV000179 Material housing: EV000402 Ambient class: IEK_V0000009

Degree of protection (IP): EV006405

Width: 6,3 Height: 45,5

Nominal Attachment Capacity: 1,5...4

Model: EV005828

Current-carrying part material: EV000149 Type of electrical connection 1: EV000415

Pret: 2,09 LEI (TVA inclus)

Detalii online: https://www.materialeelectrice.ro/clema-zni-4mm2-jxb35a-gri-309351