



IEK CLEMA ZNI-10MM2 (JXB70A) ALBASTRU

These terminal blocks serve for safe and compact connection of phase, neutral and protective (ground) conductors of various size. They are installed onto a DIN-rail. The set is completed with a marking band for number inscription and side blinds for ZNI series screw terminal blocks. Color: blue, gray, green. Terminal clamps can be covered with plastic blinds of correspondent size and color. They are made of colored non-inflammable polyamide of yellowish-green (grounding), blue (neutral), gray and green (phase) color. The set is completed with a marking band for number inscription.

They are made of colored non-inflammable polyamide. Connectable conductor cross section solid-core: 1...16

Connectable conductor cross section multi-wired: 1...10

Rated current I_n : 70

Nominal rated voltage: 600

Type of electrical connection 2: EV000415

Connection position: EV001224

Number of poles: 1

Number of clamp positions per pole: 2

Mounting method: EV005503

Material insulation body: EV000402

Operation temperature: -40...+80

Inflammability class of insulation material acc. with UL94: EV004429

Width/grid dimension: 10.5

Length: 46,0

Colour: EV000080

Nominal operating AC voltage U_e : 600

Nominal DC operating voltage U_e : 440

Nominal frequency: 50

Rated insulation voltage U_i : 660

Max. conductor cross section: 10

Material clamp: EV000179

Material housing: EV000402
Ambient class: IEK_V0000009
Degree of protection (IP): EV006405
Width: 10,5
Height: 45,5
Nominal Attachment Capacity: 4...10
Model: IEK_V0000471
Current-carrying part material: EV000149
Type of electrical connection 1: EV000415
Pret: 3,88 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/clema-zni-10mm2-jxb70a-albastru-309356>