



### IEK CLEMA ZNI-70MM2 (JXB250A) ALBASTRU

These terminal blocks serve for safe and compact connection of phase, neutral and protective (ground) conductors of various size. They are installed onto a DIN-rail. The set is completed with a marking band for number inscription and side blinds for ZNI series screw terminal blocks. Color: blue, gray, green. Terminal clamps can be covered with plastic blinds of correspondent size and color. They are made of colored non-inflammable polyamide of yellowish-green (grounding), blue (neutral), gray and green (phase) color. The set is completed with a marking band for number inscription.

They are made of colored non-inflammable polyamide. Connectable conductor cross section solid-core: 16...70

Connectable conductor cross section multi-wired: 25...70

Rated current  $I_n$ : 250

Nominal rated voltage: 600

Type of electrical connection 2: EV000415

Connection position: EV001224

Number of poles: 1

Number of clamp positions per pole: 2

Mounting method: EV005503

Material insulation body: EV000402

Operation temperature: -40...+80

Inflammability class of insulation material acc. with UL94: EV004429

Width/grid dimension: 22.2

Length: 91,0

Colour: EV000080

Nominal operating AC voltage  $U_e$ : 600

Nominal DC operating voltage  $U_e$ : 440

Nominal frequency: 50

Rated insulation voltage  $U_i$ : 660

Max. conductor cross section: 70

Material clamp: EV000179  
Material housing: EV000402  
Ambient class: IEK\_V0000009  
Degree of protection (IP): EV006405  
Width: 22,2  
Height: 61,5  
Nominal Attachment Capacity: 35...70  
Model: IEK\_V0000471  
Current-carrying part material: EV000149  
Type of electrical connection 1: EV000415  
Pret: 26,10 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/clema-zni-70mm2-jxb250a-albastru-309362>