



## **IEK GIA 06-16 BUSHINGS PENTRU SELF-SUPPORTING INSULATED CONDUCTOR S WITH A CARRYING NEUTRAL (MJPB 06-16)**

GIA bushings for self-carrying wires serve for mechanical and electrical connection of self-supporting wires. Admitted mechanical stress on the crimped connection for carrying wires makes up 40% of its tensile strength when connected to a SSIC wire and 20% in case of copper wire crimping. GIA bushings for self-carrying wires serve for mechanical and electrical connection of self-supporting wires.

Admitted mechanical stress on the crimped connection for carrying wires makes up 40% of its tensile strength when connected to a SSIC wire and 20% in case of copper wire crimping. Reduced Al nominal cross section: -

Material: EV000072

Voltage row: IEK\_V0000222

SIP section, RH part: 6.0

SIP section, LH part: 16.0

Color of RH sealed ring: EV000083

Color of left sealed ring: EV000080

Length: 73.0

Outer diameter: 18.5

Internal diameter 1: 3.3

Internal diameter 2: 5.3

Weight: 0.02

Operating temperature range: -50...+60

Application: IEK\_V0000226

Matrix Type for Sleeve Slip: IEK\_V0000223

Pret: 9,67 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/gia-06-16-bushings-pentru-self-supporting-insulated-conductor-s-with-a-carrying-neutral-mjpb-06-16-310341>