



IEK GIN54-70 BUSHINGS PENTRU SELF-SUPPORTING INSULATED CONDUCTOR S WITH A CARRYING NEUTRAL (MJPT 54-70N)

GIN bushings for wires with a carrying neutral serve for mechanical and electrical connection of phase wires within SSIC networks with a carrying neutral. Admitted mechanical stress on the crimped connection for carrying wires makes up 60% of its tensile strength. GIN bushings for wires with a carrying neutral serve for mechanical and electrical connection of neutral conductors within SSIC networks with a carrying neutral. Admitted mechanical stress on the crimped connection for carrying wires makes up 95% of its tensile strength. Reduced Al nominal cross section: -

Material: EV000072

Voltage row: IEK_V0000222

SIP section, RH part: 54.6

SIP section, LH part: 70.0

Color of RH sealed ring: EV000206

Color of left sealed ring: EV000202

Length: 175.0

Outer diameter: 25.0

Internal diameter 1: 11.0

Internal diameter 2: 10.0

Weight: 0.08

Operating temperature range: -50...+60

Application: IEK_V0000228

Matrix Type for Sleeve Slip: IEK_V0000224

Pret: 23,23 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/gin54-70-bushings-pentru-self-supporting-insulated-conductor-s-with-a-carrying-neutral-mjpt-54-70n-310369>