



### **IEK TERMOCONTRACTIBIL PSTT 5X150/240 WITH PVC ISOLATION 1KV**

PStt-1 heat-shrink sleeve is designed for connection of aluminum or copper conductors of cables with plastic, rubber and polyethylene insulation for voltage 1 kV: AVVG-1, VVG-1, AVVGz-1, VVGz-1, APvVG-1, PvVG -1, their equivalents and versions. The product's range is developed for 1-, 2-, 3-, 4- and 5-core cables. Use of high-quality two-layer heat-shrink materials with adhesive thermomelting coating on inner surfaces of external casing, tubes and multiple cable joints guarantees perfect tightness of the sleeve construction.

Wide range of products, with several versions of sleeve supply: without bushings, with bolted bushings having break-out heads, with compression bushings. Voltage row: EV004258

Model: EV004267

Number of conductors: 5

Nominal cross section conductor: 150...240

Suitable for: EV000154

Type of insulation material: IEK\_V0000184

Installation Type: IEK\_V0000187

Complete set: IEK\_V0000195

Connector Type: IEK\_V0000189

Nominal voltage: 1

Material: IEK\_V0000193

Min full shrinkage temperature: 120

Operating temperature range: -45...+50

Shrink rate: EV009535

Pret: 370,73 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/termocontractibil-pstt-5x150-240-with-pvc-isolation-1kv-310664>