



### **IEK ADAPTER TWO-BEAM TS1012 2P+PE 16A 250V IP44**

The power connectors are indispensable devices for use indoors and outdoors, together with mobile electrical equipment with cable supply system and stationary equipment of single- and three-phase types. They can be used for connection of construction electrical equipment and tools, machine-tools and other industrial equipment, power supply of workers' cabins and booths, for use in hotels, vacation houses, camp sites, etc. The bodies and insulating parts that support the current-carrying parts of the power connectors are made from heat-resistant and self-extinguishing materials.

The securely attached covers protect from ingress of dust and moisture into the connector.

Corrosion protection for springs.

Screws in mechanical and electrical connections are secured from self-unfastening.

Operation in moist environment is possible (IP44, IP54).

Special gland is available for cables of various sizes.

Free space for cable. Nominal voltage: 250

IEC-amperage: 16

Voltage acc. EN 60309-2: EV009024

Degree of protection (IP): EV006418

Clock hour position: 6

Operating voltage range: 200...250

Max. conductor cross section: 2,5

Nominal frequency: 50

Number of poles: 2

Connection system: EV001008

Cable entry: EV004016

Material: EV000139

Identification colour: EV000080

Ambient temperature: -25...+40

Angle of plug: EV000164

Number of socket outlets switchable: 2

Type of mains connection: EV005455

Pret: 61,03 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/adapter-two-beam-ts1012-2p-pe-16a-250v-ip44-311465>