



IEK PORNIRE MOTOR KMI49562 95A IN A PROTECTIVE ENCLOSURE UE=220V/AC3 IP54

KMI AC contactors with thermal electrical relay in a protective enclosure represent a complete device consisting of a compact contactor KMI, RTI thermal electrical relay, enclosure with glands and control buttons. Intended for remote actuation by means of direct connection to the network and shutting down three-phase asynchronous electric motors with a short-circuited rotor for the applied voltage limited to 400 V as well as for protecting electric motors from overloads of inadmissible duration and overcurrents arising in case of one phase retardation. Applying KMI 10910 + KMI 23211 contactors predetermines the use of a plastic enclosure; KMI 34012 + KMI 49512 are supplemented with a metal one. Correspond to the requirements of EN 60947-1, EN 60947-4-1, EN 60947-5-1. Low noise.

High electrical wear resistance.

Wide range. Rated control supply voltage U_s at AC 50HZ: 230

Rated control supply voltage U_s at DC: -

Voltage type for actuating: EV000460

Rated operation power at AC-3, 400 V: 45

Rated operation current I_e : 125

Conditioned rated short-circuit current I_q : 5

Setting range over-current release: 80...93

Connection type main current circuit: EV000415

Degree of protection (IP): EV006419

Pret: 772,63 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/contactor-kmi49562-95a-in-a-protective-enclosure-ue-220v-ac3-ip54-311663>