



IEK CONTACT EXTENSIONS PKI-11 ADDITIONAL CONTACTS 1Z+1P

PKI contact devices are intended for expanding the possibilities of contactor application within technology project automation systems. High speed response. Type of set-up: EV003970

Contactor design: ??? ?????????????? ???, ???

Voltage type for actuating: EV000509

Rated operation current I_e at AC-15, 230 V: 6.0

Rated operation current I_e at DC-13, 230 V: 1.5

Rated control supply voltage U_s at AC 50HZ: 660/400/230

Rated control supply voltage U_s at DC: 400/220

Number of contacts as normally closed contact: 1

Number of contacts as normally open contact: 1

Min on capability at min current: 10.0

Min on capability at min voltage: 24.0

Max short-term load: 100.0

Thermal resistance current: 10.0

Insulation resistance: 10.0

Rated insulation voltage U_i : 690

Max. conductor cross section: 2?2,5

Mechanical wear resistance: $1,6 \cdot 10^6$

Degree of protection (IP): EV006405

Operating temperature range: -40...+50

Ambient class: IEK_V0000010

Maintainability: EV000494

Nominal operating DC DC-13 400 V: 0.63

Nominal operating current I_e at AC-15 660 V: 1.50

Nominal operating current I_e at AC-15 400 V: 3.00

Width: 25.0

Height: 47.0

Depth: 38.0

Weight: 0.03

Pret: 15,17 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/contact-extensions-pki-11-additional-contacts-1z-1p-311843>