



### **IEK SIGNAL-ADDITIONAL CONTACT DK/AK32-02**

Auxiliary and signal auxiliary contacts in one case DK/AK32 are designed for boosting the number of supplementary contacts and overcurrent tripping alarm PRK32. Remote alarm notification and status monitoring. Compatibility: ???32

Nominal rated voltage: 24/48/60/110/230

Number of contacts as change-over contact: 0

Number of contacts as normally open contact: 0

Number of contacts as normally closed contact: 2

Nominal current AC-15 with nominal operating voltage voltage 24V: 1.50

Nominal current AC-15 with nominal operating voltage 48V: 1.00

Nominal current AC-15 with nominal operating voltage 110V: 0.50

Nominal current AC-15 with nominal operating voltage 230V: 0.30

Nominal current DC-13 with nominal operating voltage 48V: 0.30

Nominal current DC-13 with nominal operating voltage 60V: 0.15

Conditional heat current of additional contact: 6.0

Conditional heat current of emergency contact: 2.5

Rated insulation voltage  $U_i$ : 690

Rated current DC-13 at rated operating voltage 24V: 1.0

Wear resistance: 10000

Degree of protection (IP): EV006405

Side to join the PRK32: IEK\_V0000366

Type of electric connection: EV000415

Width: 9.0

Height: 91.0

Depth: 67.0

Weight: ? 0,1

Rated operation current  $I_e$  at AC-15, 230 V: 0.3

Mounting method: EV003965

Conductor cross section: 0,75...1,5  
Pret: 44,13 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/signal-additional-contact-dk-ak32-02-311984>