



AIRFAL LAMPA MEDI UMEDE,TR2, IP68, L:1574 MM,1X80W,BALAST DIMABIL

Lampa Airfal de iluminat a fost conceputa pentru a fi utilizata in principal in spatii si conditii extreme.Aceasta asigura iluminatul in locurile unde este necesara calitatea si rezistenta luminii pe termen lung.

Componentele din care este construita lampa sunt rezistente la uzura, la substante chimice (hidroclorid de amoniu, hidroxid de sodiu, acid sulfuric, acid azotat, acid fosforic, acid clorhidric, acid acetic, acid formic, acid succinic, acid lactic, acid propionic, acid valeric, acid butiric, acid caproic, acid octoic, acid decanoic, acid dodecanoic, acid tetradecanoic, acid hexadecanoic, acid octadecanoic, acid stearic, acid lauric, acid miristic, acid palmitic, acid stearic, acid arachidic, acid behenic, acid lignanic, acid cerotic, acid myristic, acid lauric, acid miristic, acid palmitic, acid stearic, acid arachidic, acid behenic, acid lignanic, acid cerotic).

Este s

le,piscine,sere,fantani,etc.



Corpul din acryl anti UV de 5 mm grosime

Reflector lucios din aluminiu

Sistem de inchidere cu surub si garnitura din elastomer termoplastic.

Suruburi de prindere inoxidabile

Putere: 220-240V, 50-60Hz

Tip Lampa T 8

IP 68 (lampa poate fi scufundata la 2 m adancime)

Rezistenta antivandalism: IK-10

Functionare la temperaturi : -20 - +55 C

Acces



| TR2 T8 1 TUBO / 2 TUBOS | | |
|-------------------------|--------|--------|
| POTENCIA (W) | L (mm) | D (mm) |
| 18 | 709 | 86 |
| 36 | 1319 | 86 |
| 58 | 1624 | 86 |

| TR2 T5 1 TUBO / 2 TUBOS | | |
|-------------------------|--------|--------|
| POTENCIA (W) | L (mm) | D (mm) |
| ALTA EFICACIA | | |
| 14 | 671 | 86 |
| 21 | 966 | 86 |
| 28 | 1272 | 86 |
| 35 | 1574 | 86 |
| ALTO RENDIMIENTO | | |
| 24 | 671 | 86 |
| 39 | 966 | 86 |
| 49 | 1574 | 86 |
| 54 | 1272 | 86 |
| 80 (Sólo 1 tubo) | 1574 | 86 |



Pret: 1.207,26 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/lampa-medi-umede-tr2-ip68-1-1574-mm-1x80w-balast-dimabil>