



IEK CONTROL BUTON LAY5-BA61 WITHOUT BIAS LIGHTING ALBASTRU 1C

Control buttons and switches are designed for an operative management of contactors (automatic tripping contactors) and automatics relay within AC electric circuits of 50 Hz and voltage limited to 600 V or DC circuits limited to 400 V and other technological processes. Various color variants provide for the most efficient arrangement of panels and boards. All devices consist of two units: removable head and contact module. Black NO contact block (1NO) and brown NC unit (1NC). Low cost, high reliability and ease of installation.

The wide range allows to complete a case of any complexity. Number of command positions: 1

Colour button: EV000080

Hole diameter: 22

Width opening: -

Height meter opening: -

Degree of protection (IP): EV006415

Type of button: EV000880

Number of contacts as normally open contact: 1

Number of contacts as normally closed contact: 0

Number of change-over contacts: 0

Number of contacts as change-over contact: 0

Type of electric connection: EV000415

Lamp socket: EV008336

Voltage type: EV000509

Number of normally open contacts: 1

Width in number of modular spacings: -

Nominal rated current: 0,6 ... 10

Nominal rated voltage: 110/230/400/600

Number of normally closed contacts: 0

Lamp type: EV008336

Pret: 12,06 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/control-buton-lay5-ba61-without-bias-lighting-albastru-1c-312139>