



### **IEK CLEME SIR ZVI-100 10-25MM2 12 PAIRS (F)**

Applied for screw connection of conductors, protecting wires from damage and excluding possibility of short circuit to the frame of electric unit. Insulation frame is made of white non-flammable polystyrene or transparent polyethylene. Terminal block and screws - latten alloy. Protection of the wire from damage and exclusion of the possibility of a short circuit to the housing of the electrical installation. Connectable conductor cross section solid-core: 10...25

Connectable conductor cross section multi-wired: 10...25

Rated current In: 100

Nominal rated voltage: 400

Type of electrical connection 2: EV000415

Connection position: EV001224

Number of poles: 12

Number of clamp positions per pole: 2

Mounting method: EV005276

Material insulation body: EV003904

Operation temperature: -25...+85

Width/grid dimension: 36.0

Length: 218

Colour: EV000202

Rated insulation voltage  $U_i$ : 450

Material clamp: EV000149

Material housing: EV000934

Ambient class: IEK\_V0000067

Degree of protection (IP): EV006404

Width: 36

Height: 28

Allowable long-term current: 100

Tightening torque Nm at conductor section: 2,5

Max operating voltage  $U_e$ : 400

Type of electrical connection 1: EV000415

Pret: 59,48 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/cleme-sir-zvi-100-10-25mm2-12-pairs-f-312921>