



IEK CLEME SIR ZVI-150 16-35MM2 12STEAM ALBASTRU

Applied for screw connection of conductors, protecting wires from damage and excluding possibility of short circuit to the frame of electric unit. Insulation frame is made of white non-flammable polystyrene or transparent polyethylene. Terminal block and screws - latten alloy. Protection of the wire from damage and exclusion of the possibility of a short circuit to the housing of the electrical installation.

Fire-retardant housing. Connectable conductor cross section solid-core: 16...35

Connectable conductor cross section multi-wired: 16...35

Rated current In: 150

Nominal rated voltage: 400

Type of electrical connection 2: EV000415

Connection position: EV001224

Number of poles: 12

Number of clamp positions per pole: 2

Mounting method: EV005276

Material insulation body: EV003904

Operation temperature: -25...+110

Width/grid dimension: 36.0

Length: 252

Colour: EV000080

Rated insulation voltage U_i : 450

Material clamp: EV000149

Material housing: EV003904

Ambient class: IEK_V0000067

Degree of protection (IP): EV006404

Width: 46

Height: 31

Allowable long-term current: 150

Tightening torque Nm at conductor section: 3,5

Max operating voltage Ue: 400

Type of electrical connection 1: EV000415

Pret: 66,53 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/cleme-sir-zvi-150-16-35mm2-12steam-albastru-312967>