



SCHRACK INTRERUPATOR GENERAL 4P 200-400A MC3 SCHRACK

L?ime net?	185,00mm
În?ime	255,00mm
Mas? net?	8,00kg.
disipare	96,00W
Temperatura minim? a mediului ambiant	-40°C
Temperatura maxim? a mediului ambiant	70°C
Echipament	Întreuptor compact
Standard	EN 60947-2
Curent nominal	400A
Tensiune nominal?	< 690VAC
Short circuit switching capacity (400V)	50kA
M?rime	3
Declan?ator	Digital electronic release - Type EM
Poli	4
Grad de poluare	3
Grad de protec?ie	IP40
Tensiune nominal? de izola?ie (Ui)	1000V
Tinere la impuls de tensiune [Uimp]	12000V
Rated ultimate short-circuit breaking capacity Icu	50kA
Rated service breaking capacity Ics	50kA
AC 380/400/415V	50kA (Icu) / 50kA (Ics)

AC 440V	50kA (Icu) / 50kA (Ics)
AC 500V	40kA (Icu) / 40kA (Ics)
AC 660/690V	12kA (Icu) / 12kA (Ics)
Durat? de via?? (Cicluri de operare)	##
AC 415V, In	4000
AC 690V, In	1500

Pret: 4.568,13 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/intrerupator-general-4p-200-400a-mc3-schrack-316654>