



SCHRACK INTREERUPATOR GENERAL 4P 160-200A MX 36KA

L?ime net?	140,00mm
În?ime	157,00mm
Mas? net?	2,65kg.
disipare	88,00W
Temperatura minim? a mediului ambiant	-40°C
Temperatura maxim? a mediului ambiant	70°C
Echipament	Întreuptor compact
Standard	EN 60947-2
Curent nominal	200A
Tensiune nominal?	< 690VAC
Short circuit switching capacity (400V)	36kA
M?rime	2
Declan?ator	Thermomagnetic release - Type A
Poli	4
Grad de poluare	3
Grad de protec?ie	IP40
Tensiune nominal? de izola?ie (Ui)	1000V
Tinere la impuls de tensiune [Uimp]	8000V
Rated ultimate short-circuit breaking capacity Icu	36kA
Rated service breaking capacity Ics	36kA
AC 380/400/415V	36kA (Icu) / 36kA (Ics)

AC 440V	36kA (Icu) / 36kA (Ics)
AC 500V	25kA (Icu) / 25kA (Ics)
AC 660/690V	6kA (Icu) / 6kA (Ics)
Durat? de via?? (Cicluri de operare)	##
AC 415V, In	6000
AC 690V, In	1500

Pret: 1.048,65 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/intrerupator-general-4p-160-200a-mx-36ka>