



**SCHNEIDER PRIZA DUBLA, NEW UNICA, COMPLETE PRIZA, 2P, 16A, EUROPEAN,  
CU OBTURATSAU, IP4X, LUCIOS, NETRATAT, ALB**

Schneider Electric New Unica socket-outlet NU206318 is a complete socket-outlet in color white with 2 socket outlets. The outlet pole configuration of this socket-outlet is 2P with shutters, ensuring safety protection. This device respects the European standard. The dielectric strength level, namely the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown or electrical discharge, is 2000V. Its rated current is 16A. The fixing mode of this device is screws. It is 85 mm in width, It is 125 mm in height, 47 mm in depth with an embedding depth of 24 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. this cover plate is AENOR, EAC, NF certified. Being environmentally friendly, this socket-outlet is a green premium product. It is mercury free.as well as heavy metal free, taking care of the environment. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.Main Range - New Unica

Product or component type - Socket-outlet

aesthetic name - Unica Studio

device presentation - Complete socket-outlet

device mounting - Flush

Socket number - 2

Outlet poles configuration - 2P

Outlet standard deviation - European

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V  
Network type - AC  
Network frequency - 50/60 Hz  
Fixing mode - Screws  
Colour tint - White (RAL 9003)  
Connections - terminals - Screw terminals  
Cable cross section - 0.5-2.5 mm<sup>2</sup> cable(s), 2 - cable stiffness: flexible  
0.5-2.5 mm<sup>2</sup> cable(s), 2 - cable stiffness: rigid  
Minimum load breaking capacity - 100 operations 1.25 I<sub>n</sub> and 1.1 I<sub>un</sub>, cos phi = 0.6  
Electrical durability - 10000 cycles, cos phi = 0.8  
Insulation resistance - > 5 MΩ at 500 V  
Dielectric strength - 2000 V  
Material - PC: mechanism cover  
Surface finish - Glossy  
Quantity per set - Set of 1 flow-pack  
Standards - IEC 60884-1  
UNE 20315-1-1  
UNE 20315-1-2  
NF C 61-314  
Product certifications - AENOR  
EAC  
NF  
Embedding depth - 24 mm  
Depth - 47 mm  
Width - 85 mm  
Height - 125 mm  
Net weight - 0.099 kg  
Surface treatment - Untreated  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
Ambient air temperature for operation - -5 to 35 °C  
Ambient air temperature for storage - -5 to 50 °C  
IK degree of protection - IK04  
IP degree of protection - IP4X  
Environmental characteristic - Acetone  
Bleach  
UV resistant  
Petrol  
Oil  
Alcohol  
Window-cleaning fluid  
Liquid soap  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1

Package 1 Height - 5 cm  
Package 1 Width - 8.5 cm  
Package 1 Length - 12.6 cm  
Package 1 Weight - 90 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 5  
Package 2 Height - 12.5 cm  
Package 2 Width - 17.5 cm  
Package 2 Length - 26 cm  
Package 2 Weight - 584 g  
Unit Type of Package 3 - S04  
Number of Units in Package 3 - 45  
Package 3 Height - 30 cm  
Package 3 Width - 40 cm  
Package 3 Length - 60 cm  
Package 3 Weight - 6.02 kg  
Pret: 35,40 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/priza-dubla-new-unica-complete-priza-2p-16a-european-cu-obturatsau-ip4x-lucios-netratat-alb-318748>