



**SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P, 10A, EUROPEAN, CU
OBTURATSAU, IP3X, LUCIOS, NETRATAT, ALB**

Schneider Electric New Unica socket-outlet NU303118 is a mechanism in color white. The outlet pole configuration of this socket-outlet is 2P with shutters, ensuring safety protection. And this device is European standard. The dielectric strength, which means the electrical strength of its insulator, is 2000V. Its rated current is 10A. The device's fixing mode is clip-in. It is 22.5 mm in width, 45 mm in height, 39.3 mm in depth with an embedding depth of 30 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. It reaches IK04 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. Being made of Cu.Zn37, PC (polycarbonate) GF10 FR material, this skin is reliable and resistant. This socket-outlet is EAC certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P

outlet standard - European

Rated current - 10 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz

Number of modules - 1 module
Fixing mode - Clip-in
Colour tint - White (RAL 9003)
Connections - terminals - Screw terminals
Cable cross section - 0.4 mm² cable(s), 2 - cable stiffness: flexible
0.4 mm² cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical durability - 10000 cycles, cos phi = 0.8
Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Material - PC: mechanism cover
PC (polycarbonate) GF10 FR: casing
CuZn37: terminals
Surface finish - Glossy
Quantity per set - Set of 1 flow-pack
Standards - IEC 60884-1
UNE 20315-1-1:1994
Product certifications - EAC
Embedding depth - 30 mm
Depth - 39.3 mm
Width - 22.5 mm
Height - 45 mm
Net weight - 0.019 kg
Surface treatment - Untreated
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - -5 to 35 A°C
Ambient air temperature for storage - -5 to 50 A°C
IK degree of protection - IK04
IP degree of protection - IP3x
Environmental characteristic - Acetone
Bleach
UV resistant
Petrol
Oil
Alcohol
Window-cleaning fluid
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 2.3 cm
Package 1 Width - 4.0 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 19.0 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 10

Package 2 Height - 5.5 cm

Package 2 Width - 14.0 cm

Package 2 Length - 26.0 cm

Package 2 Weight - 190.0 g

Unit Type of Package 3 - S04

Number of Units in Package 3 - 240

Package 3 Height - 30.0 cm

Package 3 Width - 40.0 cm

Package 3 Length - 60.0 cm

Package 3 Weight - 5.326 kg

Pret: 17,32 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-new-unica-mecanism-2p-10a-european-cu-obturatsau-ip3x-lucios-netratat-alb-318754>