



**SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P, 16A, EUROPEAN, CU
OBTURATSAU, IP4X, VOPSIT, ANTRACIT**

Schneider Electric New Unica socket-outlet NU303354 is a mechanism in color anthracite. The outlet pole configuration of this socket-outlet is 2P with shutters, ensuring safety protection. This device respects the European standard. The dielectric strength, a measure of the electrical strength of a material as an insulator, is 2000V. Its rated current is 16A. The device's fixing mode is clip-in. It is 45 mm in width, 45 mm in height and 37 mm in depth. With an embedding depth of 27.5 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. It benefits from an elegant matt finishing, constituting an added-value for your interior design. The IP rating of this device is IP21D which is very high. Besides, it reaches IK04 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. Being made of Cu.Zn37, PC (polycarbonate) GF10 FR material, this skin is reliable and resistant. This socket-outlet is AENOR, EAC, NF certified. This device is qualified as a green premium product, with minimal use of hazardous substances. This socket-outlet is mercury free New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P

outlet standard - European

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V

Network type - AC
Network frequency - 50/60 Hz
Number of modules - 2 modules
Fixing mode - Clip-in
Colour tint - Anthracite (RAL 7021)
Connections - terminals - Screw terminals
Cable cross section - 0.4 mm² cable(s), 2 - cable stiffness: flexible
0.4 mm² cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical durability - 10000 cycles, cos phi = 0.8
Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Material - PC: mechanism cover
PC (polycarbonate) GF10 FR: casing
CuZn37: terminals
Surface finish - Painted
Quantity per set - Set of 1 flow-pack
Standards - IEC 60884-1
UNE 20315-1-1
UNE 20315-1-2
NF C 61-314
Product certifications - AENOR
EAC
NF
Embedding depth - 27.5 mm
Depth - 37 mm
Width - 45 mm
Height - 45 mm
Net weight - 0.028 kg
Surface treatment - Painted
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - -5 to 35 A°C
Ambient air temperature for storage - -5 to 50 A°C
IK degree of protection - IK04
IP degree of protection - IP4X
Environmental characteristic - Acetone
Bleach
UV resistant
Petrol
Oil
Alcohol
Window-cleaning fluid
Liquid soap
Packing Units

Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4 cm
Package 1 Width - 4.5 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 29 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 8 cm
Package 2 Width - 18 cm
Package 2 Length - 25 cm
Package 2 Weight - 398 g
Unit Type of Package 3 - S03
Number of Units in Package 3 - 60
Package 3 Height - 30 cm
Package 3 Width - 30 cm
Package 3 Length - 40 cm
Package 3 Weight - 2.836 kg
Pret: 23,17 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-new-unica-mecanism-2p-16a-european-cu-obturatsau-ip4x-vopsit-antracit-318759>