



SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P E, 16A, SCHUKO, CU
OBTURATSAU, VOPSIT, ANTRACIT

Schneider Electric New Unica socket-outlet NU303754 is a mechanism in color anthracite. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. And this device is German standard. The dielectric strength level, the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown, is 2000V. Its rated current is 16A. The device's fixing mode is clip-in. It is 45 mm in width, It is 45 mm in height, and 40 mm in depth. With an embedding depth of 30.5 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. It benefits from an elegant matt finishing, constituting an added-value for your interior design. The IP rating of this device is IP21D which is very high. It reaches IK04 protection level, which can help protect against impact. This socket-outlet has screw terminals connection terminals. Being made of Cu.Zn33, Cu.Zn37, PC (polycarbonate) GF10 FR material, this socket-outlet is quite reliable and resistant. This socket-outlet is AENOR, EAC certified. This device is qualified as a green premium product, with minimal use of hazardous substances. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V
Network type - AC
Network frequency - 50/60 Hz
Number of modules - 2 modules
Fixing mode - Clip-in
Colour tint - Anthracite (RAL 7021)
Connections - terminals - Screw terminals
Cable cross section - 0.4 mm² cable(s), 2 - cable stiffness: flexible
0.4 mm² cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical durability - 10000 cycles, cos phi = 0.8
Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Material - PC: mechanism cover
PC (polycarbonate) GF10 FR: casing
CuZn37: terminals
CuZn33: earth contact
Surface finish - Painted
Quantity per set - Set of 1 flow-pack
Standards - IEC 60884-1
UNE 20315-1-1
UNE 20315-1-2
DIN VDE 0620-1
Product certifications - AENOR
EAC
Embedding depth - 30.5 mm
Depth - 40 mm
Width - 45 mm
Height - 45 mm
Net weight - 0.033 kg
Surface treatment - Painted
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - -5 to 35 A°C
Ambient air temperature for storage - -5 to 50 A°C
IK degree of protection - IK04
IP degree of protection - IP21D
Environmental characteristic - Acetone
Bleach
UV resistant
Petrol
Oil
Alcohol
Window-cleaning fluid
Liquid soap

Packing Units

Unit Type of Package 1 - PCE

Number of Units in Package 1 - 1

Package 1 Height - 4.0 cm

Package 1 Width - 4.5 cm

Package 1 Length - 4.5 cm

Package 1 Weight - 33.0 g

Unit Type of Package 2 - BB1

Number of Units in Package 2 - 10

Package 2 Height - 8.2 cm

Package 2 Width - 17.8 cm

Package 2 Length - 24.8 cm

Package 2 Weight - 431.0 g

Unit Type of Package 3 - S04

Number of Units in Package 3 - 140

Package 3 Height - 30.0 cm

Package 3 Width - 40.0 cm

Package 3 Length - 60.0 cm

Package 3 Weight - 6.8 kg

Pret: 24,36 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/priza-new-unica-mecanism-2p-e-16a-schuko-cu-obturatsau-vopsit-antracit-318766>