



**SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P E, 16A, SCHUKO, CU  
OBTURATSAU, TERMINAL FARA SURUBURI, LUCIOS, ANTIBACTERIAN, ROSU**

Schneider Electric New Unica socket-outlet NU305703 is a mechanism in color red. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. This device respects the German standard. The dielectric strength level, the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown, is 2000V. Its rated current is 16A. The device's fixing mode is clip-in. It is 45 mm in width, 45 mm in height 42 mm in depth with an embedding depth of 32 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. It reaches IK04 protection level, which can help protect against impact. Its connection terminals are screwless terminals. Being made of PC material, this socket-outlet is quite reliable and resistant. It obtained AENOR, EAC certificate. This device is qualified as a green premium product, with minimal use of hazardous substances. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

device mounting - Flush

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Schuko

Outlet standard description - Side earth

Rated current - 16 A

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V  
Network type - AC  
Network frequency - 50/60 Hz  
Number of modules - 2 modules  
Fixing mode - Clip-in  
Colour tint - Red (Pantone 1795C)  
Connections - terminals - Screwless terminals  
Cable cross section - 0.5-2.5 mm<sup>2</sup> cable(s), 2 - cable stiffness: flexible  
0.5-2.5 mm<sup>2</sup> cable(s), 2 - cable stiffness: rigid  
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6  
Electrical durability - 10000 cycles, cos phi = 0.8  
Insulation resistance - > 5 MOhm at 500 V  
Dielectric strength - 2000 V  
Material - PC: mechanism cover  
Surface finish - Glossy  
Quantity per set - Set of 1 flow-pack  
Standards - IEC 60884-1  
UNE 20315-1-1  
UNE 20315-1-2  
DIN VDE 0620-1  
Product certifications - EAC  
AENOR  
Embedding depth - 32 mm  
Depth - 42 mm  
Width - 45 mm  
Height - 45 mm  
Net weight - 0.031 kg  
Surface treatment - Antibacterial  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
Ambient air temperature for operation - -5 to 35 A°C  
Ambient air temperature for storage - -5 to 50 A°C  
IK degree of protection - IK04  
IP degree of protection - IP21D  
Environmental characteristic - Acetone  
Bleach  
UV resistant  
Petrol  
Oil  
Alcohol  
Window-cleaning fluid  
Liquid soap  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1

Package 1 Height - 4.2 cm  
Package 1 Width - 4.5 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 31 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10  
Package 2 Height - 8 cm  
Package 2 Width - 18.5 cm  
Package 2 Length - 25 cm  
Package 2 Weight - 418 g  
Unit Type of Package 3 - S03  
Number of Units in Package 3 - 60  
Package 3 Height - 30 cm  
Package 3 Width - 30 cm  
Package 3 Length - 40 cm  
Package 3 Weight - 2.949 kg  
Pret: 15,71 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-new-unica-mecanism-2p-e-16a-schuko-cu-obturatsau-terminal-fara-suruburi-lucios-antibacterian-rosu-318792>