



**SCHNEIDER PRIZA TRIPLA, NEW UNICA, MECANISM, 2P, 16A, SCHUKO, CU
OBTURATSAU, TERMINAL FARA SURUBURI, LUCIOS, NETRATAT, ALB**

Schneider Electric New Unica socket-outlet NU307618 is a mechanism in color white with 3 socket outlets.. This socket-outlet is 3 x 2P with shutters. And this device is German standard. The dielectric strength level, the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown, is 2000V. Its rated current is 16A. Clip-in this socket-outlet for the fixation. Its matching mounting box can be recessed into the surface of the wall with flush type. The surface finish is glossy, delivering an elegant and high-end feeling to a room. The IP rating of this device is IP21D which is very high. It reaches IK04 protection level, which can help protect against impact. This socket-outlet has screwless terminals connection terminals. The socket-outlet is made of PC, making it resistant and durable. It obtained DEMKO, EAC, SEMKO certificate. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Product or component type - Socket-outlet

device presentation - Mechanism

device mounting - Flush

Socket number - 3

Outlet poles configuration - 2P

outlet standard - Schuko

Outlet standard description - Side earth

Ground lug position - 45A° ground lug

Rated current - 16 A

Condition of use - Indoor

Complementary

Device application - Power supply

Cover type - With shutter

[Ue] rated operational voltage - 250 V
Network type - AC
Network frequency - 50/60 Hz
Number of modules - 6 modules
Fixing mode - Clip-in
Colour tint - White (RAL 9003)
Connections - terminals - Screwless terminals
Cable cross section - 0.5-2.5 mm² cable(s), 2 - cable stiffness: flexible
0.5-2.5 mm² cable(s), 2 - cable stiffness: rigid
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical durability - 5000 cycles, cos phi = 0.8
Insulation resistance - > 5 MOhm at 500 V
Dielectric strength - 2000 V
Material - PC: mechanism cover
PC (polycarbonate) GF10 FR: casing
Surface finish - Glossy
Quantity per set - Set of 1 flow-pack
Standards - IEC 60884-1
Product certifications - SEMKO
DEMKO
EAC
Embedding depth - 30 mm
Depth - 39.4 mm
Width - 45 mm
Height - 135 mm
Net weight - 0.106 kg
Surface treatment - Untreated
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - -5 to 35 A°C
Ambient air temperature for storage - -5 to 50 A°C
IK degree of protection - IK04
IP degree of protection - IP21D
Environmental characteristic - Acetone
Bleach
UV resistant
Petrol
Oil
Alcohol
Window-cleaning fluid
Liquid soap
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 4 cm

Package 1 Width - 4.5 cm
Package 1 Length - 13.5 cm
Package 1 Weight - 110 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10
Package 2 Height - 12 cm
Package 2 Width - 18.5 cm
Package 2 Length - 26 cm
Package 2 Weight - 1.234 kg
Unit Type of Package 3 - S04
Number of Units in Package 3 - 80
Package 3 Height - 30 cm
Package 3 Width - 40 cm
Package 3 Length - 60 cm
Package 3 Weight - 10.527 kg
Pret: 41,62 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-tripla-new-unica-mecanism-2p-16a-schuko-cu-obturatsau-terminal-fara-suruburi-lucios-netratat-alb-318872>