



SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P E, 16A, ITALIAN, CU
OBTURATSAU, LUCIOS, NETRATAT, BEJ

Schneider Electric New Unica socket-outlet NU302344 is a mechanism in color beige. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. This device respects the Italian standard. The dielectric strength, a measure of the electrical strength of a material as an insulator, is 2000V. Its rated current is 16A. Clip-in this socket-outlet for the fixation. It is 22.5 mm in width, 45 mm in height, 33 mm in depth with an embedding depth of 24 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. It reaches IP20 degree of protection which is very high. Besides, it reaches IK01 protection level, which can help protect against impact. Its connection terminals are screw terminals. Being made of ASA + PC material, this socket-outlet is quite reliable and resistant. It obtained FR.ME63.B02375 AC certificate. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements.

Main
Range - New Unica

Device application - Power supply

Product or component type - Socket-outlet

device presentation - Mechanism

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Italian

Outlet standard description - Centred earth

Complementary

Cover type - With shutter

device mounting - Flush

Rated current - 16 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz
Number of modules - 1 module
Fixing mode - Clip-in
Colour tint - Beige (RAL 1013)
Connections - terminals - Screw terminals
Cable cross section - 0.4 mm^2 cable(s), 2 - cable stiffness: flexible
 0.4 mm^2 - cable stiffness: rigid
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un, $\cos \phi = 0.6$
Electrical durability - 10000 cycles, $\cos \phi = 0.8$
Insulation resistance - $> 5 \text{ MOhm}$ at 500 V
Dielectric strength - 2000 V
Material - PC: mechanism cover
PC (polycarbonate) GF10 FR: casing
Surface finish - Glossy
Quantity per set - Set of 1 flow-pack
Standards - IEC 60884-1
Embedding depth - 24 mm
Depth - 35.5 mm
Width - 22.5 mm
Height - 45 mm
Net weight - 0.0275 kg
Surface treatment - Untreated
Resistance to chemical agents - Resistant to alcohol (70 %)
Resistant to alcohol (96 %)
Resistant to A-Lactic Acid
Resistant to diluted quaternary ammonium
Resistant to diluted bleach
Resistant to diluted ammonia
Resistant to soapy water
Resistant to crystal cleaner
Resistant to hydrogen peroxide 10 volumes
Resistant to hexane
Environment
Ambient air temperature for operation - $-5 \text{ to } 35 \text{ A}^\circ\text{C}$
Ambient air temperature for storage - $-5 \text{ to } 50 \text{ A}^\circ\text{C}$
IK degree of protection - IK01
IP degree of protection - IP21D
Environmental characteristic - Acetone
Window-cleaning fluid
UV resistant
Liquid soap
Petrol
Alcohol
Oil
Bleach
Packing Units
Unit Type of Package 1 - PCE
Number of Units in Package 1 - 1
Package 1 Height - 3.55 cm
Package 1 Width - 2.25 cm
Package 1 Length - 4.5 cm
Package 1 Weight - 27.5 g
Unit Type of Package 2 - BB1
Number of Units in Package 2 - 10

Package 2 Height - 6.5 cm
Package 2 Width - 12 cm
Package 2 Length - 18.5 cm
Package 2 Weight - 343.3 g
Unit Type of Package 3 - S03
Number of Units in Package 3 - 160
Package 3 Height - 30 cm
Package 3 Width - 30 cm
Package 3 Length - 40 cm
Package 3 Weight - 5.934 kg
Pret: 20,36 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-new-unica-mecanism-2p-e-16a-italian-cu-obturatsau-lucios-netratat-bej-318893>