



**SCHNEIDER PRIZA, NEW UNICA, MECANISM, 2P E, 16A, ITALIAN, CU**  
**OBTURATSAU, VOPSIT, ANTRACIT**

Schneider Electric New Unica socket-outlet NU302354 is a mechanism in color anthracite. The outlet pole configuration of this socket-outlet is 2P + E with shutters, ensuring safety protection. And this device is Italian standard. The dielectric strength level, namely the voltage that the material this socket-outlet uses can withstand for a given wall thickness before dielectric breakdown or electrical discharge, is 2000V. Its rated current is 16A. The device's fixing mode is clip-in. It is 22.5 mm in width, 45 mm in height and 33 mm in depth with an embedding depth of 24 mm. Its matching mounting box can be recessed into the surface of the wall with flush type. The IP rating of this device is IP20. Besides, it reaches IK01 protection level, which can help protect against impact. Its connection terminals are screw terminals. Being made of ASA + PC material, this skin is reliable and resistant. This socket-outlet is FR.ME63.B02375 AC certified. New Unica includes a suite of new designs, colors and materials. Users benefit from beautiful design that match their style and innovative products. New Unica is designed with clever features to be flexible, easy to understand and quick to install providing solutions for all customers requirements. Main

Range - New Unica

Device application - Power supply

Product or component type - Socket-outlet

device presentation - Mechanism

Socket number - 1

Outlet poles configuration - 2P + E

outlet standard - Italian

Outlet standard description - Centred earth

Complementary

Cover type - With shutter

device mounting - Flush

Rated current - 16 A

[Ue] rated operational voltage - 250 V

Network type - AC

Network frequency - 50/60 Hz  
Number of modules - 1 module  
Fixing mode - Clip-in  
Colour tint - Anthracite (RAL 7021)  
Connections - terminals - Screw terminals  
Cable cross section -  $0.4 \text{ mm}^2$  cable(s), 2 - cable stiffness: flexible  
 $0.4 \text{ mm}^2$  - cable stiffness: rigid  
Minimum load breaking capacity - 100 operations 1.25 In and 1.1 Un,  $\cos \phi = 0.6$   
Electrical durability - 10000 cycles,  $\cos \phi = 0.8$   
Insulation resistance -  $> 5 \text{ MOhm}$  at 500 V  
Dielectric strength - 2000 V  
Material - PC: mechanism cover  
PC (polycarbonate) GF10 FR: casing  
Surface finish - Painted  
Quantity per set - Set of 1 flow-pack  
Standards - IEC 60884-1  
Embedding depth - 24 mm  
Depth - 35.5 mm  
Width - 22.5 mm  
Height - 45 mm  
Net weight - 0.0275 kg  
Surface treatment - Painted  
Resistance to chemical agents - Resistant to alcohol (70 %)  
Resistant to alcohol (96 %)  
Resistant to A-Lactic Acid  
Resistant to diluted quaternary ammonium  
Resistant to diluted bleach  
Resistant to diluted ammonia  
Resistant to soapy water  
Resistant to crystal cleaner  
Resistant to hydrogen peroxide 10 volumes  
Resistant to hexane  
Environment  
Ambient air temperature for operation -  $-5 \text{ to } 35 \text{ A}^\circ\text{C}$   
Ambient air temperature for storage -  $-5 \text{ to } 50 \text{ A}^\circ\text{C}$   
IK degree of protection - IK01  
IP degree of protection - IP21D  
Environmental characteristic - Petrol  
Oil  
Acetone  
Bleach  
Window-cleaning fluid  
Alcohol  
UV resistant  
Liquid soap  
Packing Units  
Unit Type of Package 1 - PCE  
Number of Units in Package 1 - 1  
Package 1 Height - 3.55 cm  
Package 1 Width - 2.25 cm  
Package 1 Length - 4.5 cm  
Package 1 Weight - 27.5 g  
Unit Type of Package 2 - BB1  
Number of Units in Package 2 - 10

Package 2 Height - 6.5 cm  
Package 2 Width - 12 cm  
Package 2 Length - 18.5 cm  
Package 2 Weight - 343.3 g  
Unit Type of Package 3 - S01  
Number of Units in Package 3 - 40  
Package 3 Height - 15 cm  
Package 3 Width - 15 cm  
Package 3 Length - 40 cm  
Package 3 Weight - 1.573 kg  
Pret: 36,36 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/priza-new-unica-mecanism-2p-e-16a-italian-cu-obturatsau-vopsit-antracit-318894>